

Wheeled frame for Angio Ergometer w. fixation set

Original
Quality
Option

Easy installation of the Angio ergometer



Easy installation of the Angio ergometer

Wheeled frame for the Angio ergometer with fixation set (separately sold) that makes it very easy to place the ergometer over a patient bed and move it. The wheeled frame is executed with a part of instrument rail (10 * 25 mm) to conveniently connect an additional wired control unit (separately sold) during transport. Note: the wheeled frame is not compatible with former models of our Angio ergometer (9179XX). For a wheeled frame for these ergometers, contact our sales department and ask for part number 917816)



Wheeled frame for Angio Ergometer w. fixation set

Original
Quality
Option

Easy installation of the Angio ergometer

The ergometer can be used in various ergometry settings, enabling a multifunctional deployment.

Lode is a socially and environmentally responsible company. All Lode products are RoHS/WEE compliant and Lode is ISO 9001:2015, and ISO 13485:2016 certified. All medical products comply to MDD 93/42/EEC, incl. IEC 60601-1.

tests

The experience of professionals who calibrate many ergometers showed that the Lode ergometers are the most reliable across the complete workload and rpm range and still within specifications even after many years of intensive use.



Original Accessory

Accessory designed and manufactured according to the Lode company quality standards

**7
watt**

Extreme low start up load

The extreme low start-up load of 7 watts and the adjustability in small steps of 1 watt make this ergometer perfectly suitable for many different applications. The standard control unit shows multiple ergometry parameters and you can determine your specific default setting and start-up menu.



Accurate over a long period of time

The Lode ergometers are supplied with an electro-magnetic braking mechanism of Lanooy (eddy current). The biggest advantage of this braking system compared to a friction braking system is the absolute accuracy and the accuracy over time. Moreover, friction braking systems have more wearing parts.

**1
watt**

Small adjustment steps

The workload of the Lode ergometers is adjustable in steps of only 1 watt. Depending on your wishes, the test operator or the test subject can adjust the workload. The steps of 1 watt are possible in the manual mode as well as within protocols.

Specifications

Dimensions

Product length (cm)	76 cm	29.9 inch
Product width (cm)	120 cm	47.2 inch
Product height	100 cm	39.4 inch
Product weight	15 kg	33.1 lbs

Order info

Partnumber: 967800

**Specifications are subject to change without notice.*